






One-sided suspensions, side-mounted with pendling lifting

Suspension devices designed to connect working tools Ostraticky with tractor or other carrier. Without hydraulic hoses.

KLA-12Xyyy - main pin with bronze bushing, tilting pin welded in		order no.	
	KLA-12M285 - mechanical tilting, l=285 <i>(tilting range +18°/-18°)</i>	KLA12M285	
	KLA-12M335 - mechanical tilting, l=335 <i>(tilting range +18°/-18°)</i>	KLA12M335	
	KLA-12H285 - hydraulic tilting, l=285 <i>(tilting range +18°/-18°)</i>	KLA12H285	
	KLA-12H335 - hydraulic tilting, l=335 <i>(tilting range +18°/-18°)</i>	KLA12H335	

KLA-14Xyyy - main pin with bronze bushing, tilting pin with bronze bushing, fixed with expansion pin		order no.	
	KLA-14M285 - mechanical tilting, l=285 <i>(tilting range +18°/-18°)</i>	KLA14M285	
	KLA-14M335 - mechanical tilting, l=335 <i>(tilting range +18°/-18°)</i>	KLA14M335	
	KLA-14H285 - hydraulic tilting, l=285 <i>(tilting range +18°/-18°)</i>	KLA14H285	
	KLA-14H335 - hydraulic tilting, l=335 <i>(tilting range +18°/-18°)</i>	KLA14H335	

supplements and accessories		order no.	
	bracket KLA, front <i>(only for KLA-12Xyyy)</i>	CS125.491100	
	bracket KLA, rear <i>(only for KLA-12Xyyy)</i>	CS125.491200	

	<p>mounting flange KLA2 <i>(for KLA-12Xyyy)</i></p>	<p>CS125.491300</p>	
	<p>mounting flange KLA1 <i>(for KLA-14Xyyy)</i></p>	<p>CS125.491400</p>	
	<p>supporting wheel, metallic, d250 <i>(tine 50x16)</i></p>	<p>CS125.921000</p>	
	<p>wheel bracket</p>	<p>KLA00DRKOL</p>	
	<p>wheel holder, E180 <i>(for tine 50x16)</i></p>	<p>CS125.951000</p>	