







Mulching machines (high grass and scrub mowers) HM3, one-rotor



Mulching machines for mowing and mulching grass in vineyards and orchards, for mowing scrubs on pasturelands and parks, possibility of crushing strong weeds and thinner wood in vineyards and orchards or small bushes on pasturelands, direct drive without V-belts. Without drive shafts.

mulching machines for minitractors MT8-070		order no.	
	HM3-100 - MT8-070 <i>(working width 95 cm, special suspension for MT8-070)</i>	HM3100MT8	

mulching machines for compact tractors (up to 30 HP)		order no.	
	HM3-100 - T4K, MT8-132.2 <i>(working width 95 cm, special suspension for T4K, MT8-132.2)</i>	HM3100T4K	
	HM3-110 - T4K, MT8-132.2 <i>(working width 110 cm, special suspension for T4K, MT8-132.2)</i>	HM3110T4K	
	HM3-110 - kat. 1N <i>(working width 110 cm, suspension pins cat. 1N by ISO 730-2)</i>	HM3110N1	
	HM3-125 - kat. 1N <i>(working width 125 cm, suspension pins cat. 1N by ISO 730-2)</i>	HM3125N1	
	drive shaft NH01-081-VP <i>(for HM3100 and HM3110, up to 20 HP)</i>	NH01081VPJ000	
	drive shaft NH23-101-VP <i>(for HM3125, up to 30 HP)</i>	NH23101VPJ000	

mulching machines for other tractors		order no.	
	HM3-125 <i>(working width 125 cm, suspension pins cat. 1/2 by ISO 730-1)</i>	HM31250	
	HM3-135 <i>(working width 135 cm, suspension pins cat. 1/2 by ISO 730-1)</i>	HM31350	
	HM3-150 <i>(working width 150 cm, suspension pins cat. 1/2 by ISO 730-1)</i>	HM31500	
	HM3-170 <i>(working width 170 cm, suspension pins cat. 1/2 by ISO 730-1)</i>	HM31700	
	HM3-190 <i>(working width 190 cm, suspension pins cat. 1/2 by ISO 730-1)</i>	HM31900	

	<p>HM3-150 <i>(working width 150 cm, side mountable frame for 33 cm, suspension pins cat. 1/2 by ISO 730-1)</i></p>	HM3150B	
	<p>HM3-170 <i>(working width 170 cm, side mountable frame for 43 cm, suspension pins cat. 1/2 by ISO 730-1)</i></p>	HM3170B	
	<p>HM3-190 <i>(working width 190 cm, side mountable frame for 50 cm, suspension pins cat. 1/2 by ISO 730-1)</i></p>	HM3190B	
	<p>drive shaft NH04-121-VP <i>(with freewheel, clockwise)</i></p>	NH04121VPJ000	
	<p>drive shaft NH04-121-VP.J9 <i>(with freewheel, clockwise and with radial pin clutch)</i></p>	NH04121VPJ09P	

supplements and accessories		order no.	
	<p>supporting roller</p>	HM3VALEC	
	<p>supporting wheels <i>(metallic, d250, turnable, rear)</i></p>	HM3KOLA	