



Mulching machines (high grass and scrub mowers) HM4 and HM5, two-rotors

Mulching machines for mowing and mulching grass or weed controlling in vineyards and orchards, for mowing scrubs on pasturelands and parks, possibility of crushing strong weeds and thinner wood in vineyards and orchards or small bushes on pasturelands, direct drive without V-belts. Without drive shafts.

HM4 - fixed suspension		order no.	
	HM4-190p <i>(working width 190 cm, suspension pins cat. 2 by ISO 730-1)</i>	HM4190P	
	HM4-205p <i>(working width 205 cm, suspension pins cat. 2 by ISO 730-1)</i>	HM4205P	
	HM4-220p <i>(working width 220 cm, suspension pins cat. 2 by ISO 730-1)</i>	HM4220P	
	HM4-230p <i>(working width 230 cm, suspension pins cat. 2 by ISO 730-1)</i>	HM4230P	
	HM4-245p <i>(working width 245 cm, suspension pins cat. 2 by ISO 730-1)</i>	HM4245P	

HM5 - hydraulically adjustable suspension		order no.	
	HM5-245p <i>(working width 245 cm, hydraulic side shift 66 cm, suspension pins cat. 2 dle ISO 730-1)</i>	HM5245P	
	drive shaft NH05-111-VP <i>(up to 50 HP, with freewheel, clockwise)</i>	NH05111VPJ000	
	drive shaft NH05-111-VP.J9 <i>(up to 50 HP, with freewheel, clockwise and with radial pin clutch)</i>	NH05111VPJ09P	

supplements and accessories		order no.	
	Weed mowing equipment MSO-600M - mechanical side movement - floating suspension Attention! It is necessary to use separate free-flow outlet to connect this equipment.	MSO600MR	
	Weed mowing equipment MSO-600HP - hydraulic side movement - with tracer - incl. oil flow control valve 02 - floating suspension Attention! It is necessary to use two separate free-flow outlets to connect this equipment.	MSO600HPR	

	arm 60x60 for mounting the grape hoe, l=500	CS122.602600	
	sleeve for mounting the arm 60x60 on the mulching machine HM4/HM5	CS243.102032	