



## Hydraulic power units HAN

Independent hydraulic units for drive of machines and equipment Ostraticky, oil reserve 80 l, hydraulic oil flow 40, 60 or 80 l/min by 540 rpm, safety valve, backward filter, 1 pc of free-flow outlet 02F (.40, .60, .80) or 2 pcs of free-flow outlet 01M (.2x40), without oil.

hydraulic power unit HAN 80.xx		order no.	
	HAN 80.40 <i>(pump 40 l/min / 540 rpm)</i>	HAN080040	
	HAN 80.60 <i>(pump 60 l/min / 540 rpm)</i>	HAN080060	
	HAN 80.80 <i>(pump 80 l/min / 540 rpm)</i>	HAN080080	
	HAN 80.2x40 <i>(pump 2x40 l/min / 540 rpm)</i>	HAN080042	

supplements and accessories		order no.	
	oil flow control valve <i>(instead of safety valve)</i>	HANDEL	
	free-flow outlet 01M <i>(additional, with quick coupling js12,5M)</i>	HANBEZTL01M	
	free-flow outlet 01F <i>(additional, with quick coupling js12,5F)</i>	HANBEZTL01F	
	free-flow outlet 02M <i>(additional, with quick coupling js20M)</i>	HANBEZTL02M	
	free-flow outlet 02F <i>(additional, with quick coupling js20F)</i>	HANBEZTL02F	
	oil cooler	HANCHLAD	
	drive shaft NH04-081	NH04081V0J000	
	hydraulic oil cat. HM46	HANHM46	