



Passive equipment for soil cultivation and weed control along seedlings and trunks

The multipurpose equipment for soil cultivation and weed control along seedlings and trunks in vineyards or orchards, preparation of straight stripe along the plants, without movement between seedlings, for separate use or in combination, designed to connect to all Ostraticky suspensions.

Disc plough - 1-row, 1-joint				
Model	DISKPL113Zx	DISKPL113Hx	DISKPL114Zx	DISKPL114Hx
Working width [cm]	0 – 12, according to angle			
Disc [mm]	ø 360, notched	ø 360, plain	ø 410, notched	ø 410, plain
Tine dimension [mm]	70x20 / 60x20			
Lenght [cm]	36		41	
Width [cm]	20			
Height [cm]	62		64	
Version	universal, right- and left-sided			
Tractor power [kW]	min 10			
Working speed [km/h]	6 - 12			
Weight [kg]	17			

Disc plough - 1-row, 2-joint				
Model	DISKPL123Zx	DISKPL123Hx	DISKPL124Zx	DISKPL124Hx
Working width [cm]	0 – 12, according to angle			
Disc [mm]	ø 360, notched	ø 360, plain	ø 410, notched	ø 410, plain
Tine dimension [mm]	70x20 / 60x20			
Lenght [cm]	36		41	
Width [cm]	25			
Height [cm]	59		62	
Version	universal, right- and left-sided			
Tractor power [kW]	min 10			
Working speed [km/h]	6 - 12			
Weight [kg]	22			

* Listed technical data are informative, manufacturer reserves the right to change design and equipment of the machines without prior notice. The machine can be also modified according to the customer's request.

** The working speed may vary depending on the specific working conditions.

Disc plough - 2-row, 1-joint				
Model	DISKPL213Z7	DISKPL213H7	DISKPL214Z7	DISKPL214H7
Working width [cm]	20 – 40, according to angle			
Disc [mm]	ø 360, notched	ø 360, plain	ø 410, notched	ø 410, plain
Tine dimension [mm]	70x20			
Lenght [cm]	36		41	
Width [cm]	28			
Height [cm]	67		70	
Version	universal, right- and left-sided			
Tractor power [kW]	min 10			
Working speed [km/h]	6 - 12			
Weight [kg]	32			

Roller hoe				
Model	ODVBR12xxx	ODVBR21xxx	ODVBR31xxx	ODVBR41xxx
Working width [cm]	0 – 19, according to angle	10 - 27, according to angle	19 – 34, according to angle	27 – 41, according to angle
Rotary star [mm]	ø 410 / 10 spikes			
Tine dimension [mm]	60x20	70x20 / 60x20		
Lenght [cm]	47			
Width [cm]	19	28	37	48
Height [cm]	61			
Version	right-sided / left-sided			
Tractor power [kW]	min 10			
Working speed [km/h]	6 - 12			
Weight [kg]	25	33	43	54

* Listed technical data are informative, manufacturer reserves the right to change design and equipment of the machines without prior notice. The machine can be also modified according to the customer's request.

** The working speed may vary depending on the specific working conditions.

Plough for ploughing	away „E“		away „S“		towards	
Model	CS123.06 6000	CS123.06 5000	CS123.06 4000	CS123.06 3000	CS123.06 2000	CS123.06 1000
Version	left	right	left	right	left	right
Working width [cm]	25		25		23	
Tine dimension [mm]	60x20, curved		70x20, straight		70x20, straight	
Lenght [cm]	29		29		48	
Width [cm]	33		33		28	
Height [cm]	62		59		58	
Tractor power [kW]	min 10					
Working speed [km/h]	6 - 12					
Weight [kg]	16		16		19	

Stripe cultivator, two duck-foot shaped shares	
Model	PASKULT2xx
Working width [cm]	28
Share's wide [cm]	22
Lenght [cm]	48
Width [cm]	32
Height [cm]	61
Version	right-sided, left-sided
Tractor power [kW]	min 10
Working speed [km/h]	6 - 12
Weight [kg]	39

* Listed technical data are informative, manufacturer reserves the right to change design and equipment of the machines without prior notice. The machine can be also modified according to the customer's request.

** The working speed may vary depending on the specific working conditions.