



One-sided suspensions, side-mounted, with straight-line lifting

Suspension devices designed to connect working tools Ostraticky with tractor or other carrier. Including hydraulic hoses and quick couplings, hoses length up to 150 cm.

| Model | 01E | 01S | 02EM | 02EH | 02SM | 02SH |
|------------------------------|-----------|-----|------------|-----------|------------|-----------|
| Height [cm] | 64 | 77 | 64 | 64 | 77 | 77 |
| Depth [cm] | 11 | 13 | 24 | 24 | 26 | 26 |
| Width [cm] | 26 | 30 | 26 | 26 | 30 | 30 |
| Lift height [cm] | 40 | | | | | |
| Tilting | without | | mechanical | hydraulic | mechanical | hydraulic |
| Tilting range [°] | - | | +16 / -16 | | | |
| Number of hydraulic circuits | 1 | 1 | 1 | 2 | 1 | 2 |
| Oil consumption [l/min] | 10 | | | | | |
| Aggregation with tractor | interaxle | | | | | |
| Weight** [kg] | 31 | 42 | 45 | 47 | 56 | 58 |

* Listed technical data are informative, manufacturer reserves the right to change design and equipment of the machines without prior notice. The machine can be also modified according to the customer's request.

** Weights of the suspension are given without supplements and accessories.