



One-sided suspensions TBZ12

Suspension devices designed for aggregation of the working tools Ostraticky to front or rear 3-point linkage. Including hydraulic hoses and quick couplings, hoses length up to 250 cm for front, up to 150 cm for rear suspensions.

Model	TBZ12xxxxx			
	N1P	N1Z	M060P	M060Z
Aggregation with tractor	front	rear	front	rear
Suspension for 3-point linkage*	cat. 1N		cat. 1/2	
Width without arm extension**				
without tilting head [cm]	101 - 176		122 - 202	
with tilting head [cm]	110 - 185		131 - 211	
Length [cm]	21		48	
Height [cm]	43		72	
Side shift	mechanical			
Side shift range [cm]	75		80	
Tilting of working tool	without / mechanical / hydraulic			
Tilting range [°]	+16 / -16			
Number of hydraulic circuits	0 / 1			
Oil consumption [l/min]	10			
Weight without arm extension***				
without tilting head [kg]	56		90	
with tilting head [kg]	71		105	

* According to ISO 730-2, ISO 730-1.

** Arm extension 10 – 60 cm.

*** Weights are given without supplements and accessories.

**** Listed technical data are informative, manufacturer reserves the right to change design and equipment of the machines without prior notice. The machine can be also modified according to the customer's request.

Model	TBZ12xxxxx					
	H040P	H040Z	H060P	H060Z	H100P	H100Z
Aggregation with tractor	front	rear	front	rear	front	rear
Suspension for 3-point linkage*	cat. 1/2					
Width without arm extension**						
without tilting head [cm]	81 - 121		111 - 171		170 - 270	
with tilting head [cm]	90 - 130		120 - 180		179 - 279	
Lenght [cm]	48					
Height [cm]	72					
Side shift	hydraulic					
Side shift range [cm]	40		60		100	
Tilting of working tool	without / mechanical / hydraulic					
Tilting range [°]	+16 / -16					
Number of hydraulic circuits	1 / 2					
Oil consumption [l/min]	10					
Weight without arm extension***						
without tilting head [kg]	80		95		119	
with tilting head [kg]	95		110		134	

* According to ISO 730-2, ISO 730-1.

** Arm extension 10 – 60 cm.

*** Weights are given without supplements and accessories.

**** Listed technical data are informative, manufacturer reserves the right to change design and equipment of the machines without prior notice. The machine can be also modified according to the customer's request.