







## One-sided suspensions, front-mounted, with pendling lifting

Suspension devices designed to connect working tools Ostraticky with tractor or other carrier. Including hydraulic hoses and quick couplings, hoses length up to 250 cm.

suspension - front-mounted, for very narrow rows		order no.
	03m - pendling lifting, mechanical tilting <i>(suspension console with parallelogram, lift 37 cm, arm length 40 cm, tilting range +18°/-18°)</i>	KLA03M4
	03mlpo - pendling lifting, mechanical tilting <i>(suspension console without parallelogram, lift 37 cm, arm length 40 cm, tilting range +18°/-18°)</i>	KLA03M4LPO
	04m - pendling lifting, hydraulic tilting <i>(suspension console with parallelogram, lift 37 cm, arm length 40 cm, hydraulic tilting head, tilting range +18°/-18°)</i>	KLA04M4

supplements and accesories		order no.
	supporting wheel, metallic, d250, with bent tine <i>(tine 50x16)</i>	CS125.922000
	extended wheel's holder S <i>- for tine 50x16</i>	CS125.957000
	extended wheel's holder S <i>- for tine 60x20</i>	CS125.957100
	holder of the tine with duck-foot shaped share / ploughshare 60x60, l=500	CS121.010920
	holder of the tine with duck-foot shaped share / ploughshare 60x60, l=500 <i>(instead of holder of the tine with duck-foot shaped share / ploughshare 60x60, l=300)</i>	RAM606050M30
	wheel holder, E180 <i>(for tine 50x16)</i>	CS125.951000