



One-sided suspensions P12

Suspension devices designed to connect working tools Ostraticky with tractor or other carrier. Including hydraulic hoses and quick couplings, hoses length up to 250 cm for front, up to 150 cm for rear suspensions.

suspension with connecting flange		order no.	
	P12MP <i>(for front suspension, mechanical side shift 60 cm)</i>	P12M060P0	
	P12MZ <i>(for rear suspension, mechanical side shift 60 cm)</i>	P12M060Z0	
	P12H60P <i>(for front suspension, hydraulic side shift 60 cm)</i>	P12H060P0	
	P12H60Z <i>(for rear suspension, hydraulic side shift 60 cm)</i>	P12H060Z0	
	P12H100P <i>(for front suspension, hydraulic side shift 100 cm)</i>	P12H100P0	
	P12H100Z <i>(for front suspension, hydraulic side shift 100 cm)</i>	P12H100Z0	
	P12H40P <i>(for front suspension, hydraulic side shift 40 cm, necessary to use spacer)</i>	P12H040P0	
	P12H40Z <i>(for rear suspension, hydraulic side shift 40 cm, necessary to use spacer)</i>	P12H040Z0	
	spacer 150 <i>(length 15 cm)</i>	TBZ06M15	
	spacer 300 <i>(length 30 cm)</i>	TBZ06M30	
	spacer 450 <i>(length 45 cm)</i>	TBZ06M45	
	skewed spacer, front <i>(offset 28 cm to left, length 32 cm)</i>	CS125.825900	
	skewed spacer, rear <i>(offset 28 cm to left, length 47 cm)</i>	CS125.826900	

supplements and accessories see TBZ12 and N06