









Mowing brushes Horizont

The multipurpose equipment for mechanical weed control in vineyards and orchards with plastic cords or straps, working length 36 or 50 cm, brush diameter 45 cm and 41 cm. Including hydraulic hoses and quick couplings, hoses length up to 150 cm for side/rear suspension, up to 250 cm for front suspension.

Attention! It is necessary separate free-flow outlet to connect the equipment.

mowing brush, standard tracer, brush diameter 45 cm		order no.	
	Horizont 360R, cords, l=36 cm, right-sided	HOR360R0	
	Horizont 360L, cords, l=36 cm, left-sided	HOR360L0	
	Horizont 500R, cords, l=50 cm, right-sided	HOR500R0	
	Horizont 500L, cords, l=50 cm, left-sided	HOR500L0	
	Horizont 36GR, straps, l=36 cm, right-sided	HOR36GR0	
	Horizont 36GL, straps, l=36 cm, left-sided	HOR36GL0	
	Horizont 50GR, straps, l=50 cm, right-sided	HOR50GR0	
	Horizont 50GL, straps, l=50 cm, left-sided	HOR50GL0	
mowing brush, lowered tracer, brush diameter 41 cm		order no.	
	Horizont 360R, cords, l=36 cm, right-sided	HOR360RS	
	Horizont 360L, cords, l=36 cm, left-sided	HOR360LS	
	Horizont 500R, cords, l=50 cm, right-sided	HOR500RS	
	Horizont 500L, cords, l=50 cm, left-sided	HOR500LS	
	Horizont 36GR, straps, l=36 cm, right-sided	HOR36GRS	
	Horizont 36GL, straps, l=36 cm, left-sided	HOR36GLS	
	Horizont 50GR, straps, l=50 cm, right-sided	HOR50GRS	
	Horizont 50GL, straps, l=50 cm, left-sided	HOR50GLS	

supplements and accessories		order no.	
	holder of the mowing brush US <i>(for carrying arm US, length 75 cm)</i>	CS495.901000	
	suspension BasicH-M <i>- mechanical height adjustment of carrying arms</i> <i>- fixed brackets of the vertical arms</i>	BASICHM	

	<p>suspension BasicH-H1 - hydraulic height adjustment of the outer carrying arm - fixed brackets of the vertical arms</p>	right-sided	BASICHH1R	
		left-sided	BASICHH1L	
	<p>suspension BasicH-H2 - hydraulic height adjustment of both carrying arms - fixed brackets of the vertical arms</p>	BASICHH2		
	<p>tilt positioner of the vertical arm, right (instead of fixed bracket)</p>	CS410.921120		
	<p>tilt positioner of the vertical arm, left (instead of fixed bracket)</p>	CS410.921130		
	<p>holder for suspending on arm STS</p>	CS495.290010		
	<p>oil flow control valve 01</p>	DEL01		
	<p>electric operated STOP-button</p>	STOPTL1T		
	<p>electric operated STOP-button, doubled, for serial connection (only pulse switch)</p>	STOPTL3T		
	<p>electric operated STOP-button, doubled, for serial connection (pulse and permanent switch)</p>	STOPTL3Y		