



Compost turners NPK

Machines and equipment designed for small and medium sized composting areas. Compost turners - front or rear aggregation with tractors or loaders, mechanical drive 540 or 1000 r/min or hydraulic motor, rotor diamater 60 cm, supporting wheels.

mounted compost turners - with mechanical drive (for tractors)		order no.	
	mounted compost turner NPK-150T - working width 150 cm, pile height max. 100 cm - working speed 200 - 400 m/h, capacity approx. 150 - 300 m³/h - required power min. 20 kW, weight 435 kg - for front/rear linkage cat. 1 or 2 by ISO 730-1	NPK150T00	
	mounted compost turner NPK-200T - working width 200 cm, pile height max. 120 cm - working speed 200 - 400 m/h, capacity approx. 240 - 480 m³/h - required power min. 40 kW, weight 540 kg - for front/rear linkage cat. 2 by ISO 730-1	NPK200T00	
	mounted compost turner NPK-250T - working width 250 cm, pile height max. 140 cm - working speed 200 - 400 m/h, capacity approx. 350 - 700 m³/h - required power min. 60 kW, weight 625 kg - for front/rear linkage cat. 2 by ISO 730-1	NPK250T00	

mounted compost turners - with hydraulic drive (for loaders)		order no.	
	mounted compost turner NPK-150H - working width 150 cm, pile height max. 100 cm - working speed 200 - 400 m/h, capacity approx. 150 - 300 m³/h - required power min. 70 l/min / 16 MPa, weight 435 kg - including hydraulic hoses up to 150 cm, quick couplings ISO 12,5 - it is necessary to specify the exact type of carrier or the connection dimensions, when ordering	NPK150H00	
	mounted compost turner NPK-200H - working width 200 cm, pile height max. 120 cm - working speed 200 - 400 m/h, capacity approx. 240 - 480 m³/h - required power min. 70 l/min / 16 MPa, weight 540 kg - including hydraulic hoses up to 150 cm, quick couplings ISO 12,5 - it is necessary to specify the exact type of carrier or the connection dimensions, when ordering	NPK200H00	
	mounted compost turner NPK-250H - working width 250 cm, pile height max. 140 cm - working speed 200 - 400 m/h, capacity approx. 350 - 700 m³/h - required power min. 100 l/min / 16 MPa, weight 625 kg - including hydraulic hoses up to 150 cm, quick couplings ISO 12,5 - it is necessary to specify the exact type of carrier or the connection dimensions, when ordering	NPK250H00	



supplements and accessories		order no.	
	adjustable supporting wheels (2 pcs set)	NPKKOLASTMPEV	
	special hydraulic motor for pressure higher than 20 MPa	NPKHYDRM20	
	sprinkler 200 l	NPKKROP000	
	sprinkling dose regulation	NPKKROPREG	
	drive shaft NH05-071	NH05071V0J000	