



Pruning bars SLP

Pruning bars for mechanization of pruning fruit or ornamental trees and hedges, pruning with saw blades driven by the rotating hydraulic motor. Without hydraulic hoses. Can be aggregated with SLx suspension.

Attention! It is necessary separate free-flow outlet or SLOOBTVENT to connect the equipment.




pruning bars SLP			order no.
	SLP-2480H, upper <i>(2 saw blades, d450, 80 teeth, working length 90 cm)</i>	right	SLP2480RH
		left	SLP2480LH
	SLP-3480H, upper <i>(3 saw blades, d450, 80 teeth, working length 135 cm)</i>	right	SLP3480RH
		left	SLP3480LH
	SLP-4480S, vertical <i>(4 saw blades, d450, 80 teeth, working length 180 cm)</i>	right	SLP4480RS
		left	SLP4480LS
	SLP-5480S, vertical <i>(5 saw blades, d450, 80 teeth, working length 225 cm)</i>	right	SLP5480RS
		left	SLP5480LS
	SLP-2480D, lower <i>(2 saw blades, d450, 80 teeth, working length 90 cm)</i>	right	SLP2480RD
		left	SLP2480LD
	SLP-3480D, lower <i>(3 saw blades, d450, 80 teeth, working length 135 cm)</i>	right	SLP3480RD
		left	SLP3480LD




supplements and accessories			order no.
	connecting part, upper (0°-90°) <i>(with mechanical tilting)</i>	right	SLPNAKLHMR
		left	SLPNAKLHML
	connecting part, upper (0°-90°) <i>(with hydraulic tilting)</i>	right	SLPNAKLHHR
		left	SLPNAKLHHL
	connecting part, lower (0°-30°) <i>(with mechanical tilting)</i>		SLPNAKLDM



Suspension SL3

Suspension for connection of the SLA and SLP pruning bars to a tractor or another carrier. Pruning bar support, including hydraulic hoses and quick couplings, hoses length up to 250 cm for front suspension, up to 150 cm for rear suspension.

suspension SL3		order no.	
	suspension post SL3 - hydraulic lift 100 cm - pilot operated check valve of lifting cylinder	SL3SLOUP	
	carrying arm - one-sided - hydraulic side shift 40 cm - tilting -5°/+15°	mechanical tilting	SL3RAM1M
		hydraulic tilting	SL3RAM1H
	carrying arm - two-sided - hydraulic side shift 40 cm - tilting -5°/+15°	mechanical tilting	SL3RAM2M
		hydraulic tilting	SL3RAM2H

supplements and accessories		order no.	
	frame for 3-point linkage SL3 (for front 3-point linkage cat. 2 by ISO 730-1)	TBZSL3	
	frame for suspension to the tractor, front, for SL3	RAMPREDNISL30	
	mounting flange 06	RAMPREDNI06PR	