



Suspension posts US and STS

Multipurpose suspension posts designed to connect working tools Ostraticky with tractor or another carrier. Including hydraulic hoses and quick couplings, hoses length up to 250 cm.

Model	US		STS	
Lift height [cm]	0	60	60	100
Tilting of suspension post	without		mechanical / hydraulic	
Tilting range of suspension post [°]	-	-	+25 / -18	
Carrying arm	side		side / upper	
Side shift	mechanical / hydraulic			
Side shift range [cm]	32 / 40 / 60			
Tilting of working tool	mechanical / hydraulic			
Tilting range of working tool [°]	mechanical +18 / -18, hydraulic +21 / -21			
Width				
with side carrying arm [cm]	111 - 212			
with upper carrying arm [cm]	-	-	102 - 203	
Height [cm]	165		167 / 204	212
Length [cm]	34		31	
Number of hydraulic circuits	0/1/2	1/2/3	1/2/3/4	1/2/3/4
Oil consumption [l/min]	10			
Aggregation with tractor	front			
Weight				
suspension post [kg]	27	51	72 - 96	
carrying arm one-sided [kg]	34 - 47			
carrying arm double-sided [kg]	68 - 94			

* Listed technical data are informative, manufacturer reserves the right to change design and equipment of the machines without prior notice. The machine can be also modified according to the customer's request.

** Another version and combination on a request.