



Rotary stripe cultivators PPF

The multipurpose equipment for loosening soil and cultivation of inrow place in vineyards and orchards, preparation of straight stripe along the plants, it is possible to equip by hydraulic grape hoe or LPO. Carrying frame with suspension cat. 2, it is possible to change the pins for cat. 1 by ISO 730-1 on request. Including supporting wheels adjustable by motion screw.

Model	PPF450MR	PPF450xxx	PPF650xxx	PPF850xxx
Aggregation with tractor	rear	rear (S, L) / front (S)		
Suspension for 3-point linkage*	cat. 1	cat. 1/2		
Working width [cm]	45	45	65	85
Width				
„S“ - standard carrying frame [cm]	151 - 206	202 - 272	222 - 292	242 - 312
„L“ - extended carrying frame [cm]	-	262 - 392	282 - 412	302 - 432
Lenght [cm]	95	102		
Height [cm]	87	100		
Tractor power [kW]	20	20	30	40
Working speed [km/h]	3 - 6			
Weight**				
„S“ - standard carrying frame [kg]	217	255	272	289
„L“ - extended carrying frame [kg]	-	272	289	306

* According to ISO 730-1.

** Weights of the suspension are given without supplements and accessories.

*** Listed technical data are informative, manufacturer reserves the right to change design and equipment of the machines without prior notice. The machine can be also modified according to the customer's request.

**** The working speed may vary depending on the specific working conditions.