



One-sided suspensions P12

Suspension devices designed to connect working tools Ostraticky with tractor or other carrier. Including hydraulic hoses and quick couplings, hoses length up to 250 cm for front, up to 150 cm for rear suspensions.

Model	P12xxxxx							
	M060P	M060Z	H040P	H040Z	H060P	H060Z	H100P	H100Z
Aggregation with tractor	front	rear	front	rear	front	rear	front	rear
Width without arm extension*								
without tilting head [cm]	122 - 202		80 - 120		111 - 171		170 - 270	
with tilting head [cm]	131 - 211		89 - 129		120 - 180		179 - 279	
Lenght [cm]	21							
Height [cm]	20							
Side shift	mechanical		hydraulic					
Side shift range [cm]	80		40		60		100	
Tilting of working tool	without / mechanical / hydraulic							
Tilting range [°]	+16 / -16							
Number of hydraulic circuits	0 / 1		1 / 2					
Oil consumption [l/min]	10							
Weight without arm extension**								
without tilting head [kg]	61		51		66		90	
with tilting head [kg]	76		66		81		105	

* Arm extension 10 – 60 cm.

** Weights are given without supplements and accessories.

Frames for connection with a tractor				
Model	TBZ06-1	TBZ06-2	06P	06-2S
Type of connection	3-point linkage cat. 1 ***	3-point linkage cat. 1/2 ***	on a frame of carrier	on a frame of carrier
Lift height [cm]	according to 3-point linkage	according to 3-point linkage	58	60
Width [cm]	23	24	54	14
Lenght [cm]	79	88	62	57
Height [cm]	68	60	57	97
Weight [kg]	45	48	70	85

*** According to ISO 730-1.

**** Listed technical data are informative, manufacturer reserves the right to change design and equipment of the machines without prior notice. The machine can be also modified according to the customer's request.