



Automatic guiding system

Additional equipment for automatic guidance of the working tool in trunks zone in vineyards and orchards. Keeps constant distance of working tools from seedling by using tracer and hydraulic side shift. Including control box, electrical and hydraulic parts.

Attention! Requires a special construction of suspension with additional guiding elements.

One-sided version	guiding system	suspension				
Model	AuVedR1Rxx	TBZ12HxxxPA		P12HxxxPA		
		060PA	100PA	060PA	100PA	
Aggregation with tractor	-	front				
Width [cm]	93	without arm extension				
without tilting head [kg]	-	111 - 171	170 - 270	111 - 171	170 - 270	
with tilting head [kg]	-	120 – 180	179 - 279	120 – 180	179 - 279	
Lenght [cm]	150 / 180 / 210	48 21				
Height [cm]	27	72		20		
Side shift	mechanical	hydraulic				
Side shift range [cm]	53	60	100	60	100	
Tilting of working tool	-	without / mechanical / hydraulic				
Tilting range [°]	-	+16 / -16				
Number of hydraulic circuits	1/2					
Oil consumption [l/min]	min 20 – max 35					
Weight*	29	without arm extension				
without tilting head [kg]	-	96		6	67	
with tilting head [kg]	-	111 82		2		

^{*} Weights are given without supplements and accessories.

^{**} Listed technical data are informative, manufacturer reserves the right to change design and equipment of the machines without prior notice. The machine can be also modified according to the customer's request.



Double-sided version	guiding system	suspension					
Model	AuVedD20vv	NAxxxx					
	AuVedR20xx	6502	6602	6702			
Aggregation with tractor	-	front					
Width [cm]	93	without arm extension					
without tilting head [kg]	-	91 – 191	107 - 227	110 - 250			
with tilting head [kg]	-	123 - 223	139 - 258	142 - 282			
Lenght [cm]	150 / 180 / 210	29					
Height [cm]	27	35					
Side shift	mechanical	hydraulic					
Side shift range [cm]	53	2x50	2x60	2x70			
Tilting of working tool	-	without / mechanical / hydraulic					
Tilting range [°]	-	+16 / -16					
Number of hydraulic circuits	1/2						
Oil consumption [l/min]		min 20 – max 35					
Weight*	65	without arm extension					
without tilting head [kg]	-	111	125	132			
with tilting head [kg]	-	126	140	147			

^{*} Weights are given without supplements and accessories.

^{**} Listed technical data are informative, manufacturer reserves the right to change design and equipment of the machines without prior notice. The machine can be also modified according to the customer's request.